# **Technical Data Sheet**



## **Pigment Orange 13**

#### **General Information**

Color Index	Pigment Orange 13 (C.I. 21110)		
Product Code	W6212Y-1		
CAS NO.	3520-72-7		
EC No.	222-530-3		
Chemical Formula	$C_{32}H_{24}CI_2N_8O_2$		

## **Physical Properties**

Density (g/cm³)	1.31-1.60
Specific Surface Area(m <sup>2</sup> /g)	12-42
Oil Absorption (g/100g)	35-85
PH Value	4-7
Bulk Density (lb/gal)	10.9-13.36
Total impurities(ppm)	≦600

#### **Fastness Properties**

Heat Resistance (°C)	200	Alkali Resistance (1-5)	3
Light Resistance (Full Shade, 1-8)	4-5	Migration Resistance(1-5)	3
Light (Reduced tinting, 1-8)	3-4	Ethyl Acetate (1-5)	3
Weather Resistance (1-5)	2-3	Ethanol (1-5)	3
Acid Resistance (1-5)	3	MEK (1-5)	3

### **Application & Performance**

Recommended for water based ink, like water flexo printing ink, corrugated paper printing ink, carton printing ink, food and beverage printing ink etc. Yellowish grade, high color strength.

#### Note

\*Product specific and application information are based upon our current knowledge. They are non-binding and cannot be taken as guarantee. Users must establish the suitability of individual products. We do not accept any liability relating to the use of our products in particular applications.

Date of issue: Sep. 1st, 2024

TDS Version: 2.1

Tel: +86-571-83531793 Web: www.finelandchem.com