# **Technical Data Sheet**



## **Pigment Violet 23**

#### **General Information**

Color Index	Pigment Violet 23 (C.I. 51319)		
Product Code	3023R		
CAS NO.	215247-95-3		
EC No.	606-790-9		
Chemical Formula	$C_{34}H_{22}CI_2N_4O_2$		

### **Physical Properties**

Density (g/cm³)	1.40-1.60
Specific Surface Area(m²/g)	45-102
Oil Absorption (g/100g)	60-80
PH Value	6-8
Bulk Density (lb/gal)	11.7-13.3
Total impurities(ppm)	≦600

#### **Fastness Properties**

Heat Resistance (°C)	280	Alkali Resistance (1-5)	5
Light Resistance (Full Shade, 1-8)	7-8	Migration Resistance(1-5)	5
Light (Reduced tinting, 1-8)	6-7	Ethyl Acetate (1-5)	4-5
Weather Resistance (1-5)	5	Ethanol (1-5)	5
Acid Resistance (1-5)	5	MEK (1-5)	5

### **Application & Performance**

Recommended for most plastic, PVC, PP, PE, ABS, PC, PS, ABS etc. Reddish shade.

#### Note

\*Product specific and application information are based upon our current knowledge. They are non-binding and cannot be taken as guarantee. Users must establish the suitability of individual products. We do not accept any liability relating to the use of our products in particular applications.

Date of issue: Sep. 1st, 2024

TDS Version: 2.1

Tel: +86-571-83531793 Web: www.finelandchem.com