Technical Data Sheet



Pigment Yellow 168

General Information

Color Index	Pigment Yellow 168 (C.I. 13960)		
Product Code	3168		
CAS NO.	71832-85-4		
EC No.	276-057-2		
Chemical Formula	$C_{16}H_{12}CIN_4O_7S_{1/2}Ca$		

Physical Properties

Density (g/cm ³)	1.4-1.6
Specific Surface Area(m ² /g)	20-50
Oil Absorption (g/100g)	40-80
PH Value	5.0-8.0
Bulk Density (lb/gal)	23.5-35.3
Total impurities(ppm)	≦600

Fastness Properties

Heat Resistance (°C)	220-	Alkali Resistance (1-5)	4
	270	Migration Resistance(1-5)	4
Light Resistance (Full Shade, 1-8)	6-7	Ethyl Acetate (1-5)	3
Light (Reduced tinting, 1-8)	6	Ethanol (1-5)	3
Weather Resistance (1-5)	4-5	MEK (1-5)	3
Acid Resistance (1-5)	4		

Application & Performance

Recommended for plastic(LDPE, HDPE, PVC, PE, PP).

Note

*Product specific and application information are based upon our current knowledge. They are non-binding and cannot be taken as guarantee. Users must establish the suitability of individual products. We do not accept any liability relating to the use of our products in particular applications.

> Date of issue Sep 1st , 2024 TDS Version 2.1

Hangzhou Fancheng Chemical Co.,Ltd. Add NO.776, JianSheYi Road, XiaoShan, HangZhou, ZheJiang, China. Tel: +86-571-83531793 Web: www.finelandchem.com

Fineland Chem Co., Ltd. Add Room 09 27/F, Ho King Commercial Centre, 2-16 Fa Yuen Street, Mongkog, Kl, HK