

# Technical Data Sheet

## Pigment Yellow 168



FINELAND CHEM  
泛成化工

### General Information

Color Index	Pigment Yellow 168 (C.I. 13960)
Product Code	3168H
CAS NO.	71832-85-4
EC No.	276-057-2
Chemical Formula	C <sub>16</sub> H <sub>12</sub> ClN <sub>4</sub> O <sub>7</sub> S <sub>1/2</sub> Ca

### Physical Properties

Density (g/cm <sup>3</sup> )	1.4-1.6
Specific Surface Area(m <sup>2</sup> /g)	20-50
Oil Absorption (g/100g)	40-80
PH Value	5.0-8.0
Bulk Density (lb/gal)	23.5-35.3
Total impurities(ppm)	≦ 600

### Fastness Properties

Heat Resistance (°C)	220-270	Alkali Resistance (1-5)	4
Light Resistance (Full Shade, 1-8)	6-7	Migration Resistance(1-5)	4
Light (Reduced tinting, 1-8)	6	Ethyl Acetate (1-5)	3
Weather Resistance (1-5)	4-5	Ethanol (1-5)	3
Acid Resistance (1-5)	4	MEK (1-5)	3

### Application & Performance

Recommended for plastic(LDPE, HDPE, PVC, PE, PP).

### Note

\*Product specific and application information are based upon our current knowledge. They are non-binding and cannot be taken as guarantee. Users must establish the suitability of individual products. We do not accept any liability relating to the use of our products in particular applications.

Date of issue Sep. 1<sup>st</sup>, 2024

TDS Version 2.1