# **Technical Data Sheet**



## **Pigment Yellow 62**

#### **General Information**

Color Index	Pigment Yellow 62 (C.I. 13940)	
Product Code	3162H	
CAS NO.	12286-66-7	
EC No.	235-558-4	
Chemical Formula	$C_{17}H_{18}CaN_4O7_S$	

#### **Physical Properties**

Density (g/cm <sup>3</sup> )	1.20-1.78
Specific Surface Area(m <sup>2</sup> /g)	43
Oil Absorption (g/100g)	37-76
PH Value	6.5-7.5
Bulk Density (lb/gal)	10.4-11.8
Total impurities(ppm)	≦600

#### **Fastness Properties**

Heat Resistance (°C)	260	Alkali Resistance (1-5)
Light Resistance (Full Shade, 1-8)	7	Migration Resistance(1-5)
Light (Reduced tinting, 1-8)	6-7	Ethyl Acetate (1-5)
Weather Resistance (1-5)	4-5	Ethanol (1-5)
Acid Resistance (1-5)	5	MEK (1-5)

### **Application & Performance**

Recommended for plastic(PVC, LDPE, HDPE, PP).

#### Note

\*Product specific and application information are based upon our current knowledge. They are non-binding and cannot be taken as guarantee. Users must establish the suitability of individual products. We do not accept any liability relating to the use of our products in particular applications.

> Date of issue Sep. 1<sup>st</sup> , 2024 TDS Version 2.1

Hangzhou Fancheng Chemical Co.,Ltd. Add NO.776, JianSheYi Road, XiaoShan, HangZhou, ZheJiang, China. Tel: +86-571-83531793 Web: www.finelandchem.com **Fineland Chem Co., Ltd.** Add Room 09 27/F, Ho King Commercial Centre, 2-16 Fa Yuen Street, Mongkog, KI, HK